



VINYL ADHESIVE

FAST GRABBING ADHESIVE SUITABLE FOR MOST VINYL FLOORING



1L, 2L, 4L

ADVANTAGES

- Excellent Quick adhesion
- Low odour & easy to apply
- Non flammable & eco friendly
- Contains anti microbial agents
- Water based. Ready to use

DESCRIPTION:

Cemix[®] VINYL ADHESIVE is a water based adhesive which is specifically formulated for the installation of commercial and domestic vinyl floor coverings. It has high initial grab and is ideal for bonding carpets to a variety of substrates. It is non-flammable, low odour, eco-friendly, water based formulation which is easy to apply. It contains an anti microbial. This product is not suitable for Linoleum.

SUBSTRATE PREPARATION:

The substrate should be free of dust, grease, wax, oil, dirt, loose plaster, laitance, curing compounds, paint and all other friable materials and contaminants likely to prevent the adhesive from bonding. New concrete should be left with a wood float finish and sufficiently aged for a minimum of 28 days. Shiny smooth surfaces on old concrete should be acid etched or scabbled. Cemix[®] cement screeds/floor levelers/renders must be allowed to cure for a minimum of 7 days. All substrates should be structurally sound, securely fastened and properly supported to eliminate any movement, which may cause cracking. It is recommended to seal/prime surfaces.

Prime using Cemix[®] Tile Bond Latex undiluted using a roller or a brush and wait until it is tacky before applying this adhesive. Surfaces treated with waterproof membranes or some curing agents should be skimmed with a minimum of 3mm of a proprietary cementitious underlayment according to manufacturer's recommendations.

PLEASE ENSURE THERE IS NO RISING DAMP AS THIS WILL LEAD TO DELAMINATION. For further information, contact the Cemix[®] Technical support.

MIXING:

No mixing required. Use straight from the container.

APPLICATION:

Spread adhesive with the recommended notched trowel. Adhesive must be allowed to tack-up before floor covering is lowered. Tack-up time will depend upon atmospheric conditions and can be determined by placing a small piece of floor covering into the adhesive. When the floor covering is pulled away, strings of adhesive should be apparent. If no tack or holding power has developed, wait five minutes re-checking every few minutes thereafter.

If it is vinyl, complete installation according to vinyl manufacturer's instructions, ensuring the installation is rolled in both directions with the recommended roller weight, prior to the adhesive setting. Once the floor covering has been laid, they must NOT be trafficked upon or disturbed for a minimum of 24 hours at 20 °C. Allow 48 hours if temperatures fall below 20 °C or fixing over non porous substrates.

CEMIX[®] PRODUCT LTD
19 ALFRED STREET
ONEHUNGA 1061
AUCKLAND
NEW ZEALAND

0800 ASK CEMIX
WWW.CEMIX.CO.NZ



COVERAGE

SUBSTRATE	TROWEL SIZE	COVERAGE
VINYL TILES	1.6 x 1.6x 1.6mm	5m ² per L

CLEANING:

Clean all tools with water & brush immediately after use.

SAFETY:

Avoid contact with eyes & skin, both from wet & dry mix. Do not breathe in dust. Wear suitable protective clothing, gloves, eye protection & barrier cream. Wear a suitable dust mask. Wash thoroughly after handling & store any leftover material properly. FIRST AID: irrigate eyes & skin with plenty of water & seek medical advice immediately. SPILLS AND LEAKS: Keep out of sewers & storm water drains & dispose of any leftover material as trade waste in accordance with local authority guidelines.

DISCLAIMER:

Please Note: Recommendations and advice regarding the use of this product are to be taken as a guide only. Other than as appears on this products packaging, Cemix[®] Products Ltd, does not give any warranty express or implied as to the suitability of this product for your particular use, because the usage of this product is beyond the control of Cemix[®] Products Ltd, If you need advice concerning the use of, or suitability of this product for your particular application, please contact Cemix[®] Products Ltd, first. If this product is defective because of Cemix[®] Products Ltd,'s fault, please contact the supplier or Cemix[®] Products Ltd, who will replace it at no cost..

CEMIX[®] PRODUCT LTD
19 ALFRED STREET
ONEHUNGA 1061
AUCKLAND
NEW ZEALAND
0800 ASK CEMIX
WWW.CEMIX.CO.NZ

